

LEBATEX®

Aral **9206-0-PU**

END USE: Upholstery; Suitable for Commercial; Residential

COLORWAYS: Aegean, Birch, Cobblestone, Dove, Flax, Lagoon, Pearl, Rose

DESCRIPTION: A contemporary embossed design reminiscent of smooth pebbles on a beach

REPEAT: No Repeat

WIDTH: 54" wide

WEIGHT: 22.5 oz/linear yard

THICKNESS: 1.0 mm ±10%

SURFACE COMPOSITION: 100% Polyurethane

BACKING COMPOSITION: 65% Polyester, 35% Cotton

FLAME RESISTANCE: Passes NFPA 260, Cal 117, UFAC Class 1

HYDROLYSIS RESISTANCE: ISO 1419: 1995 E - 7 weeks

ABRASION: ASTM D4157 – 100,000 Double Rubs

COLORFAST TO CROCKING: AATCC 8 – Wet: Class 4 / Dry: Class 4

STRETCH: 2% x 7% at 15 lbs

SEAM SLIPPAGE: ASTM D1683-11A – 60 lbs/in x 60 lbs/in

FLEX RESISTANCE: ASTM D2097 – 25,000 cycles

BLOCKING: Fed. Std. 191A, 5872 – No. 1 - Pass

UV RESISTANCE: ASTM D4329-05 – 150 hours (Grade 4)

LEBATEX®

Aral 9206-0-PU

ADHESION: ASTM D751-06 – 4 lbs/in x 4 lbs/in

GRAB TENSILE STRENGTH: ASTM D5034-09 – 80 lbs/in x 70 lbs/in

TRAP TEAR: ASTM D2261-11 – 15 lbs/in x 12 lbs/in

COUNTRY OF ORIGIN: China

NORMAL CARE INSTRUCTIONS:

Cleaning Code W: Spot clean only with water-based shampoo or foam upholstery cleaner. Do not use solvents to spot clean. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling.



*ACT® Registered Certification Marks

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

07/01/2018