

LEBATEX®

Bermin 9205-0-SPU

END USE: Upholstery; Suitable for Hospitality

COLORWAYS: Burgundy, Café, Chocolate, Hunter, Marine, Pecan

DESCRIPTION: A small pebble texture

REPEAT: No Repeat

WIDTH: 54" wide

WEIGHT: 31 oz/linear yard

THICKNESS: 1.1 mm ±10%

SURFACE COMPOSITION: 70% PVC Foam, 25% Polyester, 5% Polyurethane

BACKING COMPOSITION: 100% Polyester

FLAME RESISTANCE: Passes NFPA 260, Cal 117

HYDROLYSIS RESISTANCE: ISO 5423:1992E - 5 weeks

ABRASION: ASTM D4157 – 80,000 Double Rubs

COLORFAST TO CROCKING: AATCC 8 – Wet: Class 4 / Dry: Class 4

STRETCH: 2% x 6% at 15 lbs

SEAM SLIPPAGE: ASTM D751-06 – 35 lbs/in x 35 lbs/in

FLEX RESISTANCE: ASTM D2097 – 25,000 cycles

BLOCKING: Fed. Std. 191A, 5872 – No. 1 - Pass

UV RESISTANCE: ASTM D4329-05 – 150 hours (Grade 4)

LEBAT[®]EX

Bermin 9205-0-SPU

ADHESION: ASTM D751-06 – 3 lbs/in x 3 lbs/in

GRAB TENSILE STRENGTH: ASTM D751-06 – 80 lbs/in x 60 lbs/in

TRAP TEAR: ASTM D751-06 – 18 lbs/in x 18 lbs/in

COUNTRY OF ORIGIN: China

NORMAL CARE INSTRUCTIONS:

Do not use chemical cleaners. Mild soap and water only.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

07/01/2018