

LEBAT<sup>EX</sup>

sta<sup>\*</sup>kleen<sup>®</sup>  
PERFORMANCE FABRIC

**Carcross  
9196-0-PU**

**END USE:** Upholstery; Suitable for Hospitality, Contract, Healthcare, Residential

**COLORWAYS:** Copper, Gold, Onyx

**DESCRIPTION:** A high sheen, large basket weave pattern

**REPEAT:** 0.75" V x 0.75" H

**WIDTH:** 54" wide

**WEIGHT:** 20.3 oz/linear yard

**THICKNESS:** 1.0 mm ±10%

**SURFACE COMPOSITION:** 100% Polyurethane

**BACKING COMPOSITION:** 85% Polyester, 15% Cotton

**FLAME RESISTANCE:** Passes NFPA 260, Cal 117, UFAC Class 1, IMO A.652(16)8.2

**HYDROLYSIS RESISTANCE:** ASTM D3690-02 - 10 weeks/ISO 1419:1995 - 10 weeks

**ABRASION:** ASTM D4157 – 100,000 Double Rubs

**COLORFAST TO CROCKING:** AATCC 8 – Wet: Class 4 / Dry: Class 4

**STRETCH:** 2% x 7% at 15 lbs

**SEAM SLIPPAGE:** ASTM D751-06 – 40 lbs/in x 40 lbs/in

**FLEX RESISTANCE:** ASTM D2097 – 25,000 cycles

**BLOCKING:** Fed. Std. 191A, 5872 – No. 1 - Pass

**UV RESISTANCE:** ASTM D4329-05 – 150 hours (Grade 4)

# LEBATEX®

starkleen®  
PERFORMANCE FABRIC

## **Carcross 9196-0-PU**

**ADHESION:** ASTM D751-06 – 4 lbs/in x 4 lbs/in

**GRAB TENSILE STRENGTH:** ASTM D751-06 – 80 lbs/in x 60 lbs/in

**TRAP TEAR:** ASTM D751-06 – 15 lbs/in x 15 lbs/in

**BLUE DYE TRANSFER RESISTANCE:** Wet: Class 4-5 / Dry: Class 4-5

**ANTI-BACTERIAL:** Pass

**MILDEW RESISTANCE:** Pass

**COLD CRACK:** (#5 Roller) -20°F

**COUNTRY OF ORIGIN:** China

### **NORMAL CARE INSTRUCTIONS:**

Cleaning Code WS: Spot clean with upholstery shampoo, foam from a mild detergent, or mild cleaning solvent. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of affected area to prevent circling.

A true stain-resistant urethane fabric created with a proprietary bonding process inherent in the manufacturing process, DEFY™ offers permanent protection. This is not a topical application: the quality will last the lifetime of the upholstery. DEFY™ is REACH and RoHS compliant, and is eligible for LEED credits for Healthcare MR Credit 5 and LEED v4 for Commercial Interiors.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

03/01/2019