

LEBATEX®

Chester 9024-0-VNL

END USE: Upholstery; Suitable for Commercial use

COLORWAYS: Chestnut, Mocha, Bittersweet, Sable

DESCRIPTION: Emulates the appearance of fine waxed pull-up leather

REPEAT: No Repeat

WIDTH: 54" wide

WEIGHT: 36 oz/linear yard

THICKNESS: 1.1 mm ±10%

SURFACE COMPOSITION: 100% PVC

BACKING COMPOSITION: 75% Polyester, 25% Cotton

FLAME RESISTANCE: Passes NFPA 260, Cal 117, UFAC Class 1, IMO A652 (16) Sec. 8.2 & 8.3, MVSS #302

ABRASION: ASTM D4157 – 50,000 Double Rubs

COLORFAST TO CROCKING: AATCC 8 – Wet: Class 4 / Dry: Class 4.5

UV RESISTANCE: ASTM D4329-05 – 200 Hours

ADHESION: ASTM D751-98 – 6 lbs/in x 4.9 lbs/in

GRAB TENSILE STRENGTH: ASTM D751-98 – 68 lbs/in x 62 lbs/in

TRAP TEAR: ASTM D5733-95 – Warp 11.2 / Fill 18.4

COLD CRACK: (#5 Roller) -10°F

COUNTRY OF ORIGIN: Taiwan

LEBATEx.

Chester 9024-0-VNL

NORMAL CARE INSTRUCTIONS:

Mild soap and water, then rinse with fresh water and wipe dry with a clean lint free cloth. For more difficult stains, wipe affected area with a soft cloth or soft bristle brush using a non-abrasive cleaner, for example Formula 409 or Fantastik. Can also be cleaned and disinfected with a 10% solution of household bleach and water. After any cleaning, always rinse with fresh water and wipe dry.

PLEASE NOTE: Folding the material and keeping it folded over long periods of time in production could result in crease marks that may not come out.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

07/01/2018