

LEBATEx.

Contender 9570-0-PVC

END USE: Upholstery; Suitable for Outdoor, Marine

COLORWAYS: Amber, Charcoal, Earth, Garnet, Midnight Blue, Mystic White, Naval Blue, Pumpkin Spice, Raven, Spring, Tan, Tobacco, Vanilla

FINISH: Anti-stain, Anti-bacterial and Anti-mildew finish

REPEAT: No Repeat

WIDTH: 55" wide

WEIGHT: 33.17 oz/linear yard

THICKNESS: 1.1 mm $\pm 10\%$

SURFACE COMPOSITION: 100% PVC

BACKING COMPOSITION: 100% Polyester

FLAME RESISTANCE: Passes NFPA 260, Cal 117-2013, UFAC Class 1, IMO 2010 Part 8, MVSS #302

ABRASION: ASTM D4157 – 500,000+ Double Rubs*

COLORFAST TO CROCKING: AATCC 8 – Wet: Class 5 / Dry: Class 5

COLORFASTNESS TO LIGHT: AATCC Method 16 (40 hours) – Class 5

SEAM SLIPPAGE: ASTM D751-06 – Warp 67 lbs x Weft 64 lbs

ANTI-BACTERIAL: Pass

MILDEW RESISTANCE: Pass

COLD CRACK: -67°F

COUNTRY OF ORIGIN: China

NORMAL CARE INSTRUCTIONS:

Cleaning Code W: Spot clean only with water-based shampoo or foam upholstery cleaner. Do not use solvents to spot clean. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling.

*Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.



5/2022

LEBATEx.COM
888.9.LEBATEx