

LEBATEX.

starkleen®  
PERFORMANCE FABRIC

**Danube**  
**9198-0-PU**

**END USE:** Upholstery; Suitable for Hospitality, Contract, Healthcare, Residential

**COLORWAYS:** Birch, Lichen, Slate

**DESCRIPTION:** An organic horizontal lined texture with metallic accents

**REPEAT:** No Repeat

**WIDTH:** 54" wide

**WEIGHT:** 22 oz/linear yard

**THICKNESS:** 1.1 mm ±10%

**SURFACE COMPOSITION:** 100% Polyurethane

**BACKING COMPOSITION:** 85% Polyester, 15% Cotton

**FLAME RESISTANCE:** Passes NFPA 260, Cal 117, UFAC Class 1, IMO A.652(16)8.2

**HYDROLYSIS RESISTANCE:** ISO 1419: 1995 E - 7 weeks

**ABRASION:** ASTM D4157 – 300,000 Double Rubs\*

**COLORFAST TO CROCKING:** AATCC 8 – Wet: Class 4 / Dry: Class 4

**STRETCH:** 2% x 2% at 15 lbs

**SEAM SLIPPAGE:** ASTM D1683-07A – 35 lbs/in x 35 lbs/in

**FLEX RESISTANCE:** ASTM D2097 – 25,000 cycles

**BLOCKING:** Fed. Std. 191A, 5872 – No. 1 - Pass

**UV RESISTANCE:** ASTM D4329-05 – 150 hours (Grade 4)

LEBATEX.

starkleen®  
PERFORMANCE FABRIC

**Danube  
9198-0-PU**

**ADHESION:** ASTM D751-89 – 4 lbs/in x 4 lbs/in

**GRAB TENSILE STRENGTH:** ASTM D5034-09 – 80 lbs/in x 80 lbs/in

**TRAP TEAR:** ASTM D5587-07 – 15 lbs/in x 15 lbs/in

**BLUE DYE TRANSFER RESISTANCE:** Wet: Class 4-5 / Dry: Class 4-5

**ANTI-BACTERIAL:** Pass

**MILDEW RESISTANCE:** Pass

**COUNTRY OF ORIGIN:** China

**NORMAL CARE INSTRUCTIONS:**

Cleaning Code WS: Spot clean with upholstery shampoo, foam from a mild detergent, or mild cleaning solvent. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of affected area to prevent circling.

\*Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

A true stain-resistant urethane fabric created with a proprietary bonding process inherent in the manufacturing process, DEFY™ offers permanent protection. This is not a topical application: the quality will last the lifetime of the upholstery. DEFY™ is REACH and RoHS compliant, and is eligible for LEED credits for Healthcare MR Credit 5 and LEED v4 for Commercial Interiors.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

03/01/2019

LEBATEX.COM  
888.9.LEBATEX