

LEBATEx™

DITTO

9014-00-PDW

END USE: Bedding, Drapery

COLORWAYS: Americano, Blue, Brown, Light Brown, Linen, Mist, Mushroom, Natural, Navy, Purple, Quartz, Slate, Stone, Sunbleach, Tweed, Wheat

DESCRIPTION: Linen “Hook Weave” Solid

REPEAT: No Repeat

WIDTH: 54”

WEIGHT: 8.2 ounces per linear yard

CONTENT: 100% Polyester

FLAME RESISTANCE – PASSES: NFPA 701

ABRASION: ASTM D4157 Wyzenbeek – 40,000 Double Rubs

BREAKING STRENGTH: ASTM D5034 – Warp: 204 lbs / Fill: 179 lbs

COLORFASTNESS TO CROCKING: AATCC Method 8 – Wet: Class 5 / Dry: Class 5

COLORFASTNESS TO LIGHT: AATCC Method 16 (60 hours) – Class 4-5

PILLING: ASTM D3512 – Class 4.5

SEAM SLIPPAGE: ASTM D434 - Warp: 48.9 lbs / Fill: 47.0 lbs

SNAGGING RESISTANCE: ASTM D3939 – Class 3.5

COUNTRY OF ORIGIN: Taiwan

NORMAL CARE INSTRUCTIONS: Ensure washer and dryer are free of any burrs, or sharp objects that can cause snagging. Machine wash warm (120 – 160 degrees Fahrenheit) at Perma-press (synthetic) cycle. Wash with like colors and products. Do not overload machine. NO fabric softeners, NO bleach, NO harsh detergents. Rinse thoroughly. Tumble dry low heat Dry cool cycle. Remove immediately. Touch Ironing at polyester setting

SEWING INSTRUCTIONS: For best results we recommend the use of “Ball – Tipped” needles and polyester thread. Adjust tensions carefully. Seams should be consistent with the specifications of ASTM D434. For complete technical details about ASTM D434: <http://astm.org>.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer’s responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

2/11/16



*ACT® Registered Certification Marks