

LEBATEx®

EVERETT 9135-00-SDW

END USE: Indoor/Outdoor Upholstery

COLORWAYS: Sea Glass, Dune, Canyon, Teak

DESCRIPTION: A soft woven textured pattern with a hand-woven heathered appearance

FINISH: Stain Repellent

REPEAT: 1.8" H x 3.2" V

WIDTH: 54" wide

WEIGHT: 14.45 oz/linear yard

CONTENT: 100% Bella-Dura® Solution Dyed Polyolefin

FLAME RESISTANCE – PASSES: NFPA 260/UFAC, Cal 117

ABRASION: ASTM D4157 Wyzenbeek – 50,000 Double Rubs

BREAKING STRENGTH: ASTM D5034 – Warp: 306 lbs/ Fill: 318 lbs

COLORFASTNESS TO CROCKING: AATCC 8—Wet: Class 5/Dry: Class 5

COLORFASTNESS TO LIGHT: AATCC16 (40 hours)—Class 4, meets or exceeds 1500 lightfast hours

PILLING: ASTM D3511 – Class 4

SEAM SLIPPAGE: ASTM D434/D3597 – Warp: 40 lbs/ Fill: 85 lbs

COUNTRY OF ORIGIN: USA

NORMAL CARE INSTRUCTIONS:

For Light Stains

A mild soap-and-water solution is all that is required for most spills. (Detergents are effective cleaners, but their harshness may affect the water-repellent characteristics.)

- 1) Apply a cleaning solution of 1 part soap to 10 parts water to the fabric.
- 2) Rinse with clear water to remove any soapy residue.*
- 3) Blot with a clean, dry cloth and allow time to air dry.
- 4) Repeat as necessary until the stain is gone.

For Stubborn Stains (Bleach Cleanable)

Some stubborn stains may require light agitation with an upholstery cleaning brush or toothbrush. Never use stiff bristles or wire brushes, as they may damage the fabric. To prevent overall soil build-up, frequent vacuuming is recommended.

- 1) Apply a cleaning solution of 1 part bleach to 4 parts water to the fabric.
- 2) Rinse with clear water to remove any bleach solution residue.*
- 3) Blot with a clean, dry cloth and allow time to air dry.

4) Repeat as necessary until the stain is gone.

*Remember to always rinse with clear water to remove all residue. Remaining residue attracts dirt, so if proper rinsing has not occurred, your fabrics will get soiled again much more quickly.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.



*ACT® Registered Certification Marks

7/28/2017