

LEBATEX.

starkleen®
PERFORMANCE FABRIC

Fractal
9200-0-PU

END USE: Upholstery; Suitable for Hospitality, Contract, Healthcare, Residential

COLORWAYS: Champagne, Lemon, Silver, Spring Mist

DESCRIPTION: A hexagonal pattern with a metallic sheen

REPEAT: 0.63" V x 0.38" H

WIDTH: 54" wide

WEIGHT: 21 oz/linear yard

THICKNESS: 0.9 mm ±10%

SURFACE COMPOSITION: 100% Polyurethane

BACKING COMPOSITION: 85% Polyester, 15% Cotton

FLAME RESISTANCE: Passes NFPA 260, Cal 117, UFAC Class 1, IMO A.652(16)8.2, FMVSS/CMVSS #302

HYDROLYSIS RESISTANCE: ASTM D3690-02 - 5 weeks / ISO 5423:1992 E - 7 weeks

ABRASION: ASTM D4157 – 300,000 Double Rubs*

COLORFAST TO CROCKING: AATCC 8 – Wet: Class 4 / Dry: Class 4

STRETCH: 2% x 6% at 15 lbs

SEAM SLIPPAGE: ASTM D751-06 – 40 lbs/in x 35 lbs/in

FLEX RESISTANCE: ASTM D2097 – 25,000 cycles

BLOCKING: Fed. Std. 191A, 5872 – No. 1 - Pass

UV RESISTANCE: ASTM D4329-05 – 150 hours (Grade 4)

LEBATEX.

starkleen®
PERFORMANCE FABRIC

**Fractal
9200-0-PU**

ADHESION: ASTM D751-06 – 4 lbs/in x 4 lbs/in

GRAB TENSILE STRENGTH: ASTM D751-06 – 80 lbs/in x 80 lbs/in

TRAP TEAR: ASTM D751-06 – 15 lbs/in x 15 lbs/in

BLUE DYE TRANSFER RESISTANCE: Wet: Class 4-5 / Dry: Class 4-5

ANTI-BACTERIAL: Pass

MILDEW RESISTANCE: Pass

COLD CRACK: (#5 Roller) -20°F

COUNTRY OF ORIGIN: China

NORMAL CARE INSTRUCTIONS:

Cleaning Code WS: Spot clean with upholstery shampoo, foam from a mild detergent, or mild cleaning solvent. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of affected area to prevent circling.

*Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

A true stain-resistant urethane fabric created with a proprietary bonding process inherent in the manufacturing process, DEFY™ offers permanent protection. This is not a topical application: the quality will last the lifetime of the upholstery. DEFY™ is REACH and RoHS compliant, and is eligible for LEED credits for Healthcare MR Credit 5 and LEED v4 for Commercial Interiors.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

03/01/2019

LEBATEX.COM
888.9.LEBATEX