

LEBATEX®

Grasmere 9220-0-PVC

END USE: Upholstery; Suitable for Commercial

COLORWAYS: Bronze, Chocolate, Ebony, Mineral, Walnut

DESCRIPTION: A subtle, lightly structured basket weave pattern

REPEAT: 3.25" V x 3.25" H

WIDTH: 54" wide

WEIGHT: 33 oz/linear yard

THICKNESS: 1.0 mm ±10%

SURFACE COMPOSITION: 100% PVC

BACKING COMPOSITION: 70% Polyester, 30% Cotton

FLAME RESISTANCE: Passes NFPA 260, Cal 117, UFAC Class 1, MVSS-302

ABRASION: ASTM D4157 – 100,000 Double Rubs

COLORFAST TO CROCKING: AATCC 8 – 20 cycles-Pass

STRETCH: 2% x 9% at 15 lbs

SEAM SLIPPAGE: ASTM D751-06 – 65 lbs/in x 65 lbs/in

FLEX RESISTANCE: ASTM D2097 – 25,000 cycles

BLOCKING: Fed. Std. 191A, 5872 – No. 1 - Pass

UV RESISTANCE: ASTM D4329-05 – 40 hours (no color change)

LEBATEX®

Grasmere 9220-0-PVC

ADHESION: ASTM D751-06 – 4 lbs/in x 4 lbs/in

GRAB TENSILE STRENGTH: ASTM D751-06 – 85 lbs/in x 90 lbs/in

TRAP TEAR: ASTM D751-06 – 15 lbs/in x 15 lbs/in

COUNTRY OF ORIGIN: China

NORMAL CARE INSTRUCTIONS:

Cleaning Code W: Spot clean only with water-based shampoo or foam upholstery cleaner. Do not use solvents to spot clean. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

07/01/2018