

# LEBATEX®

## **KISMET 9170-0-ASR**

**END USE:** Upholstery

**COLORWAYS:** Buff, Canary, Caribe, Fern, Fire, Lagoon, Marine, Pear, Pool, Sand, Teal, Wheat

**DESCRIPTION:** An attractive heathered appearance and exceptionally soft hand

**FINISH:** Stain Repellent and Acrylic Backing

**REPEAT:** No Repeat

**WIDTH:** 56" Wide

**WEIGHT:** 14.5 ounces per linear yard

**CONTENT:** 90% Polyester, 10% Nylon

**FLAME RESISTANCE – PASSES:** NFPA 260, Cal 117

**ABRASION:** ASTM D4157 – 100,000 Double Rubs

**BREAKING STRENGTH:** ASTM 5034 - Warp: 212 lbs / Fill: 151 lbs

**COLORFAST TO CROCKING:** AATCC 8 - Wet: Class.5 / Dry: Class 5

**COLORFASTNESS TO LIGHT:** AATCC Method 16 (40 hours) – Class 4

**PILLING:** ASTM D3511 – Class 5

**SEAM SLIPPAGE:** ASTM D4034 – Warp: 91 lbs / Fill: 92 lbs

**COUNTRY OF ORIGIN:** China

**NORMAL CARE INSTRUCTIONS:** To prevent overall soil, frequent vacuuming or light brushing to remove dust and grime is recommended. Spot clean using a mild water-free solvent or dry cleaning product.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.



\*ACT® Registered Certification Marks

3/12/2018

LEBATEX.COM  
888.9.LEBATEX