

LEBATEX


CONTRACT



LOOPS 9427-0-SDW

END USE: Upholstery

COLORWAYS: Azul, Midnight, Mineral, Sol

DESCRIPTION: Looping lines with a textured background

FINISH: Stain Repellent

REPEAT: 11.11" V x 7.1" H

WIDTH: 54" wide

WEIGHT: 9.56 ounces per linear yard

CONTENT: 63% Sunbrella® Acrylic, 37% Sunbrella® Polyester

FLAME RESISTANCE – PASSES: NFPA 260, CAL 117

ABRASION: ASTM D4157 – 60,000 Double Rubs

BREAKING STRENGTH: ASTM 5034 – Warp: 333.27 lbs / Fill: 364.77 lbs

COLORFASTNESS TO CROCKING: AATCC Method 8 – Wet: Class 5 / Dry: Class 5

COLORFASTNESS TO LIGHT: AATCC Method 16 (2,000 hours)

PILLING: ASTM D3511 – Class 4

SEAM SLIPPAGE: ASTM D434 – Warp: 81.80 lbs / Fill: 73.53 lbs

SUSTAINABILITY: Facts – Silver Level NSF/ANSI 336; Greenguard Gold; HPD Certified

COUNTRY OF ORIGIN: USA

NORMAL CARE INSTRUCTIONS:

For Light Stains

1. Remove dried or excess stain by lightly brushing, scraping, or vacuuming, taking care not to abrade or damage the fabric.
2. Lift as much liquid spill as possible with a dry, clean cloth, using a blotting or rolling motion to avoid pressing the liquid into the fabric.
3. Saturate the stain and surrounding area of the fabric with water and cleaner.
4. Use a sponge, clean towel, or soft bristle brush to loosen the stain being careful not to abrade the fabric.
5. Rinse thoroughly to remove all cleaning agent residue.
6. Vacuum or blot excess water with a clean towel.
7. Let the fabric air dry.
8. Repeat until the stain is completely removed, or proceed to Stubborn Stains below.

For Stubborn Stains

1. Add 1 cup of bleach and 1/4 cup of soap to 1 gallon of warm water.
2. Saturate the affected area using the cleaning solution.
3. Use a sponge, clean towel, or soft bristle brush to loosen the stain.
4. Rinse thoroughly to remove all cleaning agent residue.
5. Vacuum or blot excess water with a clean towel.
6. Let the fabric air dry.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.



* Certification Marks owned by the Association for Contract Textiles, Inc.