

LEBATEx™

NEVILLE 9473-0-NVL

END USE: Upholstery

FINISH: Acrylic Backing and Alta™

REPEAT: No Repeat

WIDTH: 54"

WEIGHT: 1.05 pounds per linear yard

CONTENT: 100% Polyester

FLAME RESISTANCE – PASSES: NFPA 260, Cal 117

ABRASION: ASTM D4157 Wyzenbeek – 100,000 Double Rubs

BREAKING STRENGTH: ASTM D5034 – Warp: 416 lbs / Fill: 312 lbs

PILLING: ASTM D3511 – Class 3

SEAM SLIPPAGE: ASTM D4034 – Warp: 104 lbs / Fill: 105 lbs

COUNTRY OF ORIGIN: China

NORMAL CARE INSTRUCTIONS: Spot clean only with water-based shampoo or foam upholstery cleaner. Do not use solvents to spot clean. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling.

*Please note due to the printing process the width of finished, printed fabric may vary up to +/- 5%.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.



*ACT® Registered Certification Marks