

LEBATEx®

Plateau 9204-0-PU

END USE: Upholstery; Suitable for Commercial; Residential

COLORWAYS: Apple, Ash, Black, Bronze, Burgundy, Chestnut, Chocolate, Doe, Green Tea, Ivy, Lava, Lichen, Linen, Mango, Maple, Peacock, Persimmon, Plum, Saffron, Sea

DESCRIPTION: A classic leather feel with a muted distressed look

REPEAT: No Repeat

WIDTH: 54" wide

WEIGHT: 20 oz/linear yard

THICKNESS: 1.0 mm ±10%

SURFACE COMPOSITION: 100% Polyurethane

BACKING COMPOSITION: 100% Polyester

FLAME RESISTANCE: Passes NFPA 260, Cal 117, UFAC Class 1, IMO A.652(16)8.2, FMVSS/CMVSS #302

HYDROLYSIS RESISTANCE: ASTM D3690-02 - 7 weeks / ISO 1419:1995 E - 7 weeks

ABRASION: ASTM D4157 – 100,000 Double Rubs

COLORFAST TO CROCKING: AATCC 8 – Wet: Class 4 / Dry: Class 4

STRETCH: 10% x 20% at 15 lbs

SEAM SLIPPAGE: ASTM D751-06 – 40 lbs/in x 40 lbs/in

FLEX RESISTANCE: ASTM D2097 – 25,000 cycles

BLOCKING: Fed. Std. 191A, 5872 – No. 1 - Pass

UV RESISTANCE: ASTM D4329-05 – 150 hours (Grade 4)

LEBATEX®

Plateau 9204-0-PU

ADHESION: ASTM D751-06 – 4 lbs/in x 4 lbs/in

GRAB TENSILE STRENGTH: ASTM D751-06 – 50 lbs/in x 50 lbs/in

TRAP TEAR: ASTM D751-06 – 18 lbs/in x 18 lbs/in

COUNTRY OF ORIGIN: China

NORMAL CARE INSTRUCTIONS:

Cleaning Code W: Spot clean only with water-based shampoo or foam upholstery cleaner. Do not use solvents to spot clean. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

07/01/2018