

LEBATEx®

RAW SILK 1115-0-RSL

END USE: Drapery

WIDTH: 59" wide

WEIGHT: 5.4 ounces per linear yard

CONTENT: 100% Polyester

FLAME RESISTANCE – PASSES: NFPA 701

SEAM SLIPPAGE: ASTM D434/D3597 - Warp: 48 lbs./Fill: 53.5 lbs.

COUNTRY OF ORIGIN: China

NORMAL CARE INSTRUCTIONS: Ensure washer and dryer are free of any burrs, or sharp objects that can cause snagging. Machine wash warm (120 – 160 degrees Fahrenheit) at Perma-press (synthetic) cycle. Wash with like colors and products. Do not overload machine. NO fabric softeners, NO bleach, NO harsh detergents. Rinse thoroughly. Tumble dry low heat Dry cool cycle. Remove immediately. Touch Ironing at polyester setting.

*Please note due to the printing process the width of finished, printed fabric may vary up to +/- 5%.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.



*ACT® Registered Certification Marks

7/1/2018

LEBATEx.COM
888.9.LEBATEx