

# LEBATEX®

## Rhine 9203-0-SPU

**END USE:** Upholstery; Suitable for Hospitality

**COLORWAYS:** Black, Brown, Charcoal, Stone, Topaz

**DESCRIPTION:** A gravel-like texture

**REPEAT:** No Repeat

**WIDTH:** 54" wide

**WEIGHT:** 31 oz/linear yard

**THICKNESS:** 1.1 mm ±10%

**SURFACE COMPOSITION:** 70% PVC Foam, 25% Polyester, 5% Polyurethane

**BACKING COMPOSITION:** 100% Polyester

**FLAME RESISTANCE:** Passes NFPA 260, Cal 117

**HYDROLYSIS RESISTANCE:** ISO 5423:1992E - 5 weeks

**ABRASION:** ASTM D4157 – 80,000 Double Rubs

**COLORFAST TO CROCKING:** AATCC 8 – Wet: Class 4 / Dry: Class 4

**STRETCH:** 2% x 6% at 15 lbs

**SEAM SLIPPAGE:** ASTM D751-06 – 35 lbs/in x 35 lbs/in

**FLEX RESISTANCE:** ASTM D2097 – 25,000 cycles

**BLOCKING:** Fed. Std. 191A, 5872 – No. 1 - Pass

**UV RESISTANCE:** ASTM D4329-05 – 150 hours (Grade 4)

# LEBATEX®

## Rhine 9203-0-SPU

**ADHESION:** ASTM D751-06 – 3 lbs/in x 3 lbs/in

**GRAB TENSILE STRENGTH:** ASTM D751-06 – 80 lbs/in x 60 lbs/in

**TRAP TEAR:** ASTM D751-06 – 18 lbs/in x 18 lbs/in

**COUNTRY OF ORIGIN:** China

**NORMAL CARE INSTRUCTIONS:**

Do not use chemical cleaners. Mild soap and water only.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

07/01/2018