



Rills 9215-0-PVC

END USE: Upholstery; Suitable for Commercial; Outdoor/Marine

COLORWAYS: Apple, Charcoal, Lime, Sun, Turquoise

DESCRIPTION: A tight twill texture

REPEAT: No Repeat

WIDTH: 54" wide

WEIGHT: 36.6 oz/linear yard

THICKNESS: 1.25 mm \pm 10%

SURFACE COMPOSITION: 100% PVC

BACKING COMPOSITION: 100% Polyester

FLAME RESISTANCE: Passes NFPA 260, Cal 117, UFAC Class 1, IMO A652 (16) Sec. 8.2 & 8.3, MVSS #302, Boston Fire Dept. IX-1, FAA FAR 25.853, NFPA 701 Small Scale

ABRASION: ASTM D4157 – 500,000 Double Rubs*

COLORFAST TO CROCKING: AATCC 8 – Wet: Class 4 / Dry: Class 4

COLORFASTNESS TO LIGHT: 650 hours

COLORFASTNESS TO WATER/SEA: Shade Change -5 / Staining -5

STRETCH: 7% x 21% at 15 lbs

SEAM SLIPPAGE: ASTM D751-06 – 55 lbs/in x 41 lbs/in

FLEX RESISTANCE: ASTM D2097 – 25,000 cycles

BLOCKING: Fed. Std. 191A, 5872 – No. 1 - Pass



Rills 9215-0-PVC

ADHESION: ASTM D751-06 – 4 lbs/in x 3 lbs/in

GRAB TENSILE STRENGTH: ASTM D751-06 – 114 lbs/in x 99 lbs/in

TRAP TEAR: ASTM D751-06 – 40 lbs/in x 59 lbs/in

PINK STAIN: Pass

ANTI-BACTERIAL: Pass

MILDEW RESISTANCE: Pass

COLD CRACK: (#5 Roller) -20°F

COUNTRY OF ORIGIN: China

NORMAL CARE INSTRUCTIONS:

Cleaning Code W: Spot clean only with water-based shampoo or foam upholstery cleaner. Do not use solvents to spot clean. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling.

*Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

This product does not comply with California Bill AB-2998.



*ACT® Registered Certification Marks

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

02/07/2020