



SARATOGA 9571-0-PVC

END USE: Upholstery

COLORWAYS: Ash, Claret, Clove, Coal, Mule, Saddle, Tombstone, Tortilla

DESCRIPTION: A two-tone classic leather look with a timeless appeal

REPEAT: No Repeat

FINISH: Ink and Stain Resistant

WIDTH: 54" wide

WEIGHT: 22 oz/linear yard

THICKNESS: 1.0 mm \pm 10%

SURFACE COMPOSITION: 100% PVC

BACKING COMPOSITION: 100% Polyester

FLAME RESISTANCE: Passes NFPA 260, Cal 117, UFAC Class 1, IMO 2010 Part 8, Section 3.1, MVSS #302

ABRASION: ASTM D4157 – 100,000 Double Rubs

COLORFAST TO CROCKING: AATCC 8 – Wet: Class 4.5 / Dry: Class 4.5

UV STABILITY: 250 hours, Grade 4.5

STRETCH: 7% x 30% at 15 lbs

SEAM SLIPPAGE: ASTM D751-06 – Passes 35 lbs/in x 35 lbs/in

FLEX RESISTANCE: ASTM D2097 – 25,000 cycles

BLOCKING: Fed. Std. 191A, 5872 – No 1 - Pass

ADHESION: ASTM D751-06 – 4 lbs/in x 4 lbs/in

GRAB TENSILE STRENGTH: ASTM D751-06 – 110 lbs/in x 110 lbs/in

TRAP TEAR: ASTM D751-06 – Passes 35 lbs/in x 35 lbs/in

COUNTRY OF ORIGIN: China



SARATOGA 9571-0-PVC

NORMAL CARE INSTRUCTIONS:

GENERAL CLEANING: Ordinary dirt, smudges and water-soluble stains such as coffee, tea, juice, soft drinks, milk, beer, and wine can be removed with mild soap and water. Use a clean cloth or soft sponge to gently wipe the stain with soapy water. Don't stop there – it's really important to remove any remaining soap solution by wiping the area with a cloth and clean water, and finally to dry the surface with a soft lint-free cloth or towel. Avoid cleaners containing abrasives, as these can damage the product's coating. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel.

DIFFICULT STAINS: Although Ez-Kleen performance fabrics are resistant to most common stains, the dyes and pigments in some staining agents have the ability to create a permanent stain if not treated properly. To clean difficult stains from Ez-Kleen upholstery use a household cleaner such as Formula 409® All-Purpose Spray Cleaner. After cleaning rinse the area with fresh water then dry with a clean, lint-free cloth. If a ghost stain remains, use a solvent-type cleaner, such as rubbing alcohol (isopropyl alcohol-91%). Rinse the cleaned area with fresh water then dry with a clean, lint-free cloth.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

10/1/2020