

# LEBATEx™

## SEQUENCE 9068-00-INC

**END USE:** Upholstery

**COLORWAYS:** Opal, Silver, Night, Peridot, Teal, Cobalt, Violet, Fuchsia, Crimson, Burnt Sienna and Bittersweet

**DESCRIPTION:** Textured weave with metallic accents

**FINISH:** Incase® and Acrylic Backing

**REPEAT:** No Repeat

**WIDTH:** 54"

**WEIGHT:** 13.33 ounces per linear yard

**CONTENT:** 43% Polyester, 40% Acrylic, 17% Rayon

**FLAME RESISTANCE – PASSES:** NFPA 260, Cal 117

**ABRASION:** ASTM D4157 Wyzenbeek – 80,000 Double Rubs

**BREAKING STRENGTH:** ASTM D5034 – Warp: 50 lbs / Fill: 50 lbs

**COLORFASTNESS TO CROCKING:** AATCC 8 – Wet: Class 3 / Dry: Class 4

**COLORFASTNESS TO LIGHT:** AATCC 16 (40 hours) – Class 4

**PILLING:** ASTM D3511 – Class 3

**SEAM SLIPPAGE:** ASTM D4034 – Warp: 79 lbs / Fill: 70 lbs

**COUNTRY OF ORIGIN:** USA

**NORMAL CARE INSTRUCTIONS:** As recommended by Crypton. For additional information, please refer to the Crypton website at <http://crypton.com/support/cleaning-care/contract-fabrics-finishes/>

**Spot Cleaning:** The spot cleaning method of stain removal can be used for most light to medium stains.

1. Before spot cleaning, blot up liquids on the surface with a clean, soft towel and brush off any loose dirt.
2. Prepare a cleaning solution of ¼ tsp mild enzyme detergent, such as Tide®, Woolite® or Dawn® dishwashing liquid, per 1 cup of lukewarm water.
3. Apply the cleaning solution to the affected area using a spray bottle.
4. Work the solution into the affected area by lightly scrubbing the area with a sponge or soft bristle brush. Make sure to work from the outside of the stain inward so as not to spread the stain and rinse your sponge or brush frequently.
5. Rinse thoroughly to remove all soap residues, as residues will attract dirt. Blot excess moisture with a clean, soft towel or sponge.
6. Repeat steps 3-6 as needed.
7. Allow fabric to air dry.

For overall cleaning, it is recommended to use a hot water extraction cleaning method as part of the regular maintenance routine based on traffic and usage.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

4/21/16



\*ACT® Registered Certification Marks