

LEBATEx.

SKYLINE 9093-0-YDW

END USE: Drapery

COLORWAYS: Blue, Brown, Gold, Opal

DESCRIPTION: A subtle statement, Skyline has a beautiful tonal brushstroke quality

REPEAT: 13.8" V x 13.2" H

WIDTH: 66"

WEIGHT: 9.42 ounces per linear yard

CONTENT: 100% Polyester

FLAME RESISTANCE – PASSES: NFPA 701

COLORFASTNESS TO CROCKING: AATCC 8— Wet: Class 5/Dry: Class 5

COLORFASTNESS TO LIGHT: AATCC16 (60 hours) — Class 4.5

SEAM SLIPPAGE: ASTM D434/D3597 – Warp: 47.8 lbs / Fill: 45.2 lbs

COUNTRY OF ORIGIN: Korea

NORMAL CARE INSTRUCTIONS NORMAL CARE INSTRUCTIONS:

Clean liquid spills quickly with a clean, dry cloth: For liquid spills, gently blot (don't rub) spill immediately with an absorbent cloth while spill is still fresh. Wipe off with clean water and a clean, dry cloth if needed.

For semi-solid spills, try to lift the spot off of the fabric: Working in a circular motion or removing the spill from the side is often the best means to lift spills from the fabric. Change towel surface frequently until spot has been transferred off of the fabric and onto the absorbent cleaning cloth. Try to avoid pressing the spill or spreading the stain. Wipe off with clean water and a clean, dry cloth if needed.

For semi-solid spills, try to lift the spot off of the fabric: If a spill does not come off with water and a clean, dry cloth, add a mild detergent mixed with water and repeat circular motion. Mild detergents such as Sport Wash, Tide Free, or Cheer Free work best. If a stain remains, a solvent may be needed to remove the stubborn stain. It is recommended to use odorless mineral spirits, dry cleaning fluid such as perchloroethylene or Fantastik Orange Action All Purpose Cleaner. Bleach can also be used on cleanable fabrics. Wipe off with water and a dry clean cloth. Do not rub harshly. The harder you rub when cleaning a spill, the deeper the soil can be pushed into the fibers. Remove all soap or cleaning agent residue from the surface with clean water.

SEWING INSTRUCTIONS:

For best results we recommend the use of "Ball – Tipped" needles and polyester thread. Adjust tensions carefully. Seams should be consistent with the specifications of ASTM D434. For complete technical details about ASTM D434: <http://astm.org>

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.



4/18/2017