



## STANDING OVATION 9542-0-CYP

**END USE:** Upholstery

**COLORWAYS:** Copper, Denim, Mulberry, Olive, Steel

**FINISH:** Crypton®

**REPEAT:** 11.75" V x 14.375" H

**WIDTH:** 54" wide

**WEIGHT:** 16 ounces per linear yard

**CONTENT:** 57% Polyester, 43% Olefin

**FLAME RESISTANCE – PASSES:** NFPA 260, Cal 117

**ABRASION:** ASTM D4157 – 54,000 Double Rubs

**COLORFASTNESS TO CROCKING:** Wet: Class 4.5 / Dry: Class 5

**COLORFASTNESS TO LIGHT:** AATCC Method 16 (40 hours) – Class 4

**PILLING:** ASTM D3511 – Class 4

**SEAM SLIPPAGE:** ASTM D4034 – Warp: 61 lbs / Fill: 54 lbs

**BREAKING STRENGTH:** ASTM D5034 – Warp: 178 lbs / Fill: 328 lbs

**COUNTRY OF ORIGIN:** USA

### **NORMAL CARE INSTRUCTIONS:**

**Clean liquid spills quickly with a clean, dry cloth:** For liquid spills, gently blot (don't rub) spill immediately with an absorbent cloth while spill is still fresh. Wipe off with clean water and a clean, dry cloth if needed.

**For semi-solid spills, try to lift the spot off of the fabric:** Working in a circular motion or removing the spill from the side is often the best means to lift spills from the fabric. Change towel surface frequently until spot has been transferred off of the fabric and onto the absorbent cleaning cloth. Try to avoid pressing the spill or spreading the stain. Wipe off with clean water and a clean, dry cloth if needed.

**For semi-solid spills, try to lift the spot off of the fabric:** If a spill does not come off with water and a clean, dry cloth, add a mild detergent mixed with water and repeat circular motion. Mild detergents such as Sport Wash, Tide Free, or Cheer Free work best. If a stain remains, a solvent may be needed to remove the stubborn stain. It is recommended to use odorless mineral spirits, dry cleaning fluid such as perchloroethylene or Fantastik Orange Action All Purpose Cleaner. Wipe off with water and a dry clean cloth. Do not rub harshly. The harder you rub when cleaning a spill, the deeper the soil can be pushed into the fibers. Remove all soap or cleaning agent residue from the surface with clean water.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations

