

LEBATEx®

SULLIVAN 9151-0-SUL

END USE: Bedding, Drapery, Upholstery

DESCRIPTION: Double Sided Chenille

REPEAT: No Repeat

WIDTH: 59" wide

WEIGHT: 13.6 ounces per linear yard

CONTENT: 100% Polyester

FLAME RESISTANCE – PASSES: NFPA 701, NFPA 260, CAL TB 117, CAN/ULC S109

ABRASION: ASTM D4157 – 50,000 Double Rubs

BREAKING STRENGTH: ASTM D5034 - Warp: 198 lbs / Fill: 103 lbs

PILLING: ASTM D3511 – Class 5

SNAGGING: ASTM D3939 – Class 5

SEAM SLIPPAGE: ASTM D434 –Warp: 48.5 lbs/ Fill: 53 lbs

TEAR STRENGTH: ASTM D2261 - Warp: 7.9 lbs / Fill: 6.1 lbs

COUNTRY OF ORIGIN: Mexico

NORMAL CARE INSTRUCTIONS:

Ensure washer is free of any burrs, or sharp objects that can cause snagging. Machine wash cold (65 - 85 degrees Fahrenheit) at Perma-press (synthetic) cycle. Wash with like colors and products. Do not overload machine. NO fabric softeners, NO bleach, NO harsh detergents. Rinse thoroughly. Do not iron.

*Please note due to the printing process the width of finished, printed fabric may vary up to +/- 5%.

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.



*ACT® Registered Certification Marks

7.1.2019

Page 1 of 1

LEBATEx.COM
888.9.LEBATEx