

# LEBAT<sup>®</sup>EX

## Tarim 9214-0-PVC

**END USE:** Upholstery; Suitable for Commercial

**COLORWAYS:** Copper, Marlin, Oyster, Pearl, Sedona, Sesame

**DESCRIPTION:** A faux leather shagreen design with a smooth pebbled texture

**REPEAT:** No Repeat

**WIDTH:** 54" wide

**WEIGHT:** 33 oz/linear yard

**THICKNESS:** 1.0 mm ±10%

**SURFACE COMPOSITION:** 100% PVC

**BACKING COMPOSITION:** 70% Polyester/30% Cotton

**FLAME RESISTANCE:** Passes NFPA 260, Cal 117, UFAC Class 1, MVSS-302

**ABRASION:** ASTM D4157 – 100,000 Double Rubs

**COLORFAST TO CROCKING:** AATCC 8 – Wet: Class 4 / Dry: Class 4

**STRETCH:** 2% x 9% at 15# MD

**SEAM SLIPPAGE:** ASTM D751-06 – 65 lbs/in x 65 lbs/in

**FLEX RESISTANCE:** ASTM D2097 – 25,000 cycles

**BLOCKING:** Fed. Std. 191A, 5872 – No. 1 - Pass

**UV RESISTANCE:** ASTM D4329-05 – 150 hours (Grade 4)

# LEBATEX®

## Tarim 9214-0-PVC

**ADHESION:** ASTM D751-06 – 4 lbs/in x 4 lbs/in

**GRAB TENSILE STRENGTH:** ASTM D751-06 – 85 lbs/in x 90 lbs/in

**TRAP TEAR:** ASTM D751-06 – 15 lbs/in x 15 lbs/in

**COUNTRY OF ORIGIN:** China

**NORMAL CARE INSTRUCTIONS:**

Cleaning Code W: Spot clean only with water-based shampoo or foam upholstery cleaner. Do not use solvents to spot clean. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling.



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

All fabric subject to dye lot variations.

07/01/2018